

cannon

D-Subminiature Product Overview



ITT

ENGINEERED FOR LIFE

D-Subminiature Connectors

Key Markets & Applications

ITT Cannon's D-Subminiature product line is engineered to perform in the harshest environments. Originally designed for aircraft radio systems, Cannon's D-Subminiature became the first multi-purpose interconnect solution of its kind, ideal for multiple markets and applications. From rocket launches and satellite systems, to rugged military transports and commercial avionics, its versatility has made this Cannon invention the most widely used connector in the world.





Space & Satellites



Military Vehicles



Commercial Avionics








D*M, D*MM, D*MA with NM, NMB option connectors are used when non magnetic characteristics are required.

Hermetic Military D connectors are designed to meet environmental conditions of extreme pressure differential.

These high reliability D-Sub connectors are the finest quality connectors and are designed to be comparable to 24308-style connectors.

	D*NM Series	D*H	24308-Style
Space	X	X	
Military/Aerospace	X	X	X
Medical/Food Processing	X	X	
Mass Transit	X		
Industrial	X	X	
Telecom			
Wire Gauge Range AWG	AWG 18 - 28	up to AWG 20	AWG 18 - 30
Mating Cycles	50, 200, 500	500	500
RoHS Compliant	available	no	no
Layout	9, 15, 25, 37, 50, 15, 26, 44, 62, 78, 104 (high density) and Combo D	9, 15, 25, 37, 50	9, 15, 25, 37, 50, 15, 26, 44, 62, 78, 104 (high density)
Dielectric Withstanding Voltage (1)	1000 VAC	750 VAC	1000 VAC
Current Rating (Amps)	7.5 A max.	7.5 A max.	7.5 A max.
Contact Resistance	10 milli Ohm max.	15 milli Ohm max.	10 milli Ohm max. (Signal Contacts)
Operating Temperature	-55°C/125°C	-54°C/125°C	-50°C/150°C
Salt Spray Test Resistance in Hours	48 hrs	48 hrs	48 hrs
Shell			
Material	copper alloy	low carbon steel	steel
Finish	gold over copper	electro-deposited tin over cadmium over copper flash	yellow chromate over cadmium or zinc
Insulator			
Material	Thermoplastic, UL 94V-0	compression glass	Thermoplastic, type PCT UL 94V-0
Color	white or black	n/a	black
Contact	machined	machined	machined
Material	copper alloy	steel	copper alloy
Finish	gold over copper	electro-deposited tin over cadmium over copper flash	1.27 µm gold over nickel
Contact Termination/Styles			
Crimp	X		X
Solder Pot	X	X	X
Straight Solder	X		X
Right Angled Solder	X		X
IDC (insulation displacement connection)			
Wire Wrap			X
Coax	X		
Fiber Optic	X		
High Power	X		
High Voltage	X		
Press Fit			
Eyelet		X	

(1) at sea level



D*MAM crimp connectors are designed to be comparable to 24308-style connectors (except for documentation).

D*MM straight PCB connectors are designed to be comparable to 24308-style versions (except for documentation).

GD* connectors provide high-density and moisture protection.



2D connectors feature double the contact density in the same insert area.

D*MA crimp connectors are designed to be comparable to 24308-style connectors (except for finishes).

D*M straight PCB connectors are designed to be comparable to 24308-style connectors (except for finishes).

A broad range of D-Sub connectors are available with stainless steel shells for corrosion resistance.

D*MAM	D*MM	GD*	2D	D*MA	D*M	Stainless Steel
						X
X	X	X	X	X	X	X
						X
X	X	X		X	X	X
			X	X	X	X
AWG 18 - 30	AWG 20 - 28	AWG 20	AWG 22 -2 6	AWG 20 - 28	AWG 20 - 28	AWG 18 - 30
500	500	500	500	200, 500	50, 200, 500	50, 200, 500
available	available	no	available	available	available	yes
9, 15, 25, 37, 50, 15, 26, 44, 62, 78,104 (high density)	9, 15, 25, 37, 50	9, 15, 25, 37, 50, 15, 26, 44, 62, 78,104 (high density)	19, 31, 52, 79, 100	9, 15, 25, 37, 50, 15, 26, 44, 62, 78,104 (high density)	9, 15, 25, 37, 50	9, 15, 25, 37, 50, 15, 26, 44, 62, 78,104 (high density) and Combo D
1000 VAC	1000 VAC	1000 VAC	1000 VAC	1000 VAC	1000 VAC	1000 VDC
7.5 A max.	7.5 A max.	7.5 A max. (Standard Density)	5 A max. 2A max. (BR Series)	7.5 A max.	7.5 A max.	7.5 A max.
10 milli Ohm max. (Signal Contacts)	10 milli Ohm max. (Signal Contacts)	10 milli Ohm max.	9 milli Ohm max.	10 milli Ohm max.	7.5 milli Ohm max.	10 milli Ohm max.
-50°C/150°C	-50°C/150°C	-65°C/150°C	-55°C/125°C	-55°C/125°C	-55°C/125°C	-55°C/125°C
48 hrs	48 hrs	48 hrs	48 hrs	48 hrs	48 hrs	48 hrs
steel	steel	low carbon steel	low carbon steel/brass	steel	steel	stainless steel
RoHS - Tin/Nickel yellow chromate over cadmium or zinc	RoHS - Tin/Nickel yellow chromate over cadmium or zinc	yellow chromate over cadmium or zinc	yellow chromate over cadmium	RoHS - Tin/Nickel yellow chromate over cadmium or zinc	RoHS - Tin/Nickel yellow chromate over cadmium or zinc	passivated
Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0	glass filled nylon	Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0
black	black	white or black	black	white	black	black or white
machined	machined	machined	twist pin	machined	machined	machined
copper alloy	copper alloy	copper alloy	copper alloy	copper alloy	copper alloy	copper alloy
1.27 µm gold over nickel	1.27 µm gold over nickel	gold over nickel	gold plate	gold over nickel	gold over nickel	gold over nickel
X		X	X	X		X
	X				X	X
X	X		X	X	X	X
X	X		X	X	X	X
	X				X	X
						X
						X
						X
						X



Series D*JT planar array filter connectors provide excellent protection against EMI and RFI.

D*NE are special low profile 90° solder pin connectors according to the CECC75 301 802 Eurostyle.


D*NG pressfit connectors provide a low-cost alternative to traditional through hole solder contacts (straight only).

Speedy D connectors terminate ribbon cables without stripping and without splicing.

The D*W connector provides IDC technology. Stranded or solid wires could be terminated.

D*U is a low-cost, crimp type D-Subminiature series.

D*JT	D*NE	D*NG	D*SF	D*W	D*U
X					
X	X	X	X	X	X
X			X	X	
AWG 8 - 26	-	-	AWG 26 - 28	AWG 20 - 30	AWG 18 - 30
200, 500	50, 200, 500	50, 200, 500	50, 200, 500	50, 200, 500	50, 200, 500
no	yes	yes	yes	yes	available
9, 15, 25, 37, 50 2W2, 2WK2, 3W3, 3WK3, 5W5	9, 15, 25, 37	9, 15, 25, 37, 50	9, 15, 25, 37	9, 15, 25, 37	9, 15, 25, 37, 50
500 VDC	1000 VAC	1200 VAC	780 VAC	1000 VAC	1000 VAC
5.0 A max. (Signal contacts) 40 A max. (High power contacts)	5 A at 25°C 3.5 A at 70°C	5.0 A at 25°C 3.5 A at 70°C	1.5 A max.	3.0 A (AWG 20) - 0.8 A (AWG 30)	5.0 A max.
10 milli Ohm max. (Signal Contacts)	25 milli Ohm max.	10 milli Ohm max.	15 milli Ohm max.	15 milli Ohm max.	15 milli Ohm max.
-55°C/125°C	-55°C/125°C	-55°C/125°C	-55°C/125°C	-55°C/125°C	-55°C/125°C
20 hrs	12 hrs	20 hrs	20 hrs	20 hrs	20 hrs
steel	steel	steel	steel	steel	steel
tin	tin	tin	tin	tin	RoHS - Tin/Nickel yellow chromate over cadmium
Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0	glass filled Thermoplastic, type PCT UL 94V-0
black	black	black	black	black	black
machined	stamped	stamped	stamped	stamped	stamped or machined
copper alloy	copper alloy	copper alloy	copper alloy	copper alloy	copper alloy
gold over nickel	gold over nickel	gold over nickel (standard); gold over PdNi	gold over nickel	gold over nickel in contact area, balance tin	gold over nickel
					X
X					
X					X
X	X				
			X	X	
X		X			



D* connectors are available for high performance uses according to DIN 41652.

Filter connector series D*JK are designed for commercial applications, providing EMI/RFI protection.

ZD* connectors are available for applications where price is the primary driver.

ZD*A high density connectors are available for applications where price is the primary driver.

D*A crimp connectors are available for applications where price is the primary driver.

Combo D connectors offer an industry standard shield I/O interconnect, with the flexibility of a customized special.

D*	D*JK	ZD*	ZD*A	D*A	Combo D
					X
X					X
X	X	X	X	X	X
	X	X	X	X	
AWG 20 - 28	AWG 20 - 28	AWG 20 - 28	AWG 24 - 26	AWG 20 - 28	AWG 8 - 26
50, 200, 500	200, 500	50, 200	50, 200	50, 200	50, 200, 500
yes	no	yes	yes	yes	yes (Mil: no)
9, 15, 25, 37, 50	9, 15, 25, 37, 50	9, 15, 25, 37, 50	15, 26, 44, 62, 78	9, 15, 25, 37, 50	E: 2W2; 2WK2; 5W1 A: 3W3; 3WK3; 7W2; 11W1 B: 5W5; 9W4; 13W3; 17W2; 21W1 C: 8W8; 13W6; 17W5; 21WA4; 25W3; 27W2 D: 24W7; 36W4; 43W2; 47W1
1250 VAC	250 VDC	1000 VAC	500 VAC	500 VAC	varies
5.0 A at 25°C 3.5 A at 70°C	5.0 A max.	5.0 A max.	2.0 A max.	5.0 A max.	7.5 A max. (Signal contacts) 5.0 A max. (Coaxial contacts) 65 A max. (HEP) 5.0 A max. (HV contacts)
10 milli Ohm max.	10 milli Ohm max. (Signal contacts)	20 milli Ohm max.	15 milli Ohm max.	15 milli Ohm max.	10 milli Ohm max. (Signal contacts)
-55°C/125°C	-55°C/125°C	-55°C/105°C	-55°C/105°C	-55°C/105°C	-55°C/125°C (Mil: 150°C)
20 hrs	20 hrs	12 hrs	12 hrs	12 hrs	20 hrs (Mil: 48 hrs)
steel	steel	steel	steel	steel	steel
tin	tin	tin	tin	tin	tin
Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0	glass filled Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0	Thermoplastic, type PCT UL 94V-0
black	white	black	black	black	black
machined	machined	stamped	stamped	stamped	machined
copper alloy	copper alloy	brass (male) phosphore bronze (female)	copper alloy	copper alloy	copper alloy
gold over nickel	gold over nickel	gold over nickel in contact area, balance tin	gold over nickel	gold over nickel	gold over nickel
			X	X	X
X	X	X	X		X
X	X	X	X		X
X	X	X	X		X
X					
					X
					X
					X
					X
					X

Cannon Combo-D Part Number Configurator

US Version

	DBM	E	9C4	P	J	K87
Product Family Designator D*M = Solder Cup (Industrial & Space/Non-Magnetic) D*MM = Solder Cup (Military / Hi-Rel, 50 microinch gold plating) D*A = Crimp						
Hardware Modifier blank = .120" (3.05mm) Through Hole C = 90° Metal Bracket, #4-40 Fastener and Boardlock D = 90° Metal Bracket, #4-40 Fastener and #4-40 Screwlock E = #4-40 Clinchnut G = 90° Metal Bracket, #4-40 Fastener, #4-40 Screwlock, Boardlock H = .300" (7.6mm) Standoff, #4-40 Screwlock J = 90° Metal Bracket, M3 Fastener, M3 Screwlock, Boardlock K = .162" (4.11mm) Through Hole L = 90° Metal Bracket, M3 Fastener, Boardlock N = .300" (7.6 mm) Standoff, #4-40 Screwlock, Boardlock O = 90° Metal Bracket, M3 Fastener, M3 Screwlock P = 90° Metal Bracket, #4-40 Fastener Q = .300" (7.6 mm) M3 Standoff S = 90° Metal Bracket, M3 Fastener T = .300" (7.6 mm) M3 Standoff U = .300" (7.6 mm) Standoff, M3 Screwlock and Boardlock V = .300" (7.6 mm) #4-40 Standoff W = .300" (7.6mm) Standoff, M3 Screwlock X = M3 Clinchnut Y = Dual Float Mount Z = .300" (7.6mm) #4-40 Standoff, Boardlock						
Shell Material and Plating Modification Code blank = Carbon steel, Yellow chromate over zinc A101 = Carbon steel, Yellow chromate over cadmium A197 = Carbon steel, Pure Tin over Nickel (socket side only) RoHS K87 = Carbon steel Pure Tin over Nickel (pin shell with grounding dimples) RoHS F225 = Stainless steel, Passivated RoHS NMBK52 = Gold plated, non-magnetic for space applications						
Contact Termination Code blank = Solder cup (D*M/D*MM), Crimp (D*A) J = 90° PCB signal contact, (ø.030" × .170" long) N = Straight PCB signal contact, (ø.030" × .178" long) V = 90° PCB signal contact, (ø.024" × .157" long) Y = Straight PCB signal contact, (ø.024" × .178" long)						
Contact Gender P = Pin /Male (plug) S = Socket /Female (receptacle)						
Layout (Example: 5W1- Total number of 5 contacts with 1 size 8 cavity) Shell Size E: 2W2, 2WK2, 5W1 Shell Size A: 3W3, 3WK3, 7W2, 11W1 Shell Size B: 5W5, 9W4, 13W3, 17W2, 21W1 Shell Size C: 8W8, 13W6, 17W5, 21WA4, 25W3, 27W2 Shell Size D: 24W7, 36W4, 43W2, 47W1 W = Empty size 8 cavities C = 75 Ohm Coax installed (straight or 90°) X = 50 Ohm Coax installed (straight or 90°) H = High power installed (straight) P = High power installed (Euro, 90°only) V = High voltage installed (available in straight PC only) G = Guide pin or guide socket installed R = Mini High Power 90° installed E = HEP Contact (installed or loose)						

Cannon Combo-D Part Number Configurator

European Version

DBM	E	9C4	P	P00	1A5N	A191	K87	146
Product Family Designator D*M = D*M Combo-D * = Shell size – E, A, B, C and D				PCB Mounting Method 146 = Pushfit for PCB hole dia. 3,0 mm 161 = Pushfit for PCB hole dia. 3,2 mm, straight version only 162 = Pushfit for PCB hole dia. 3,2 mm, 90° version only				
Hardware Modifier blank = 3,05mm (.120") Through Hole E = #4-40 Clinchnut (solder cup, straight solder pin and 1A0N) N = 7,66 mm (.300") with #4-40 post and pushfit, only OL4 Q = 7,66 mm (.300") M3 standoff, only OL4 T = 7,66 mm (.300") M3 post, only OL4 U = 7,66 mm (.300") standoff, M3 Post with pushfit, only OL4 V = 7,66 mm (.300") #4-40 standoff, only OL4 X = M-3 Clinchnut (solder cup, straight solder pin and 1A0N) Y = Dual Float Mount, only solder cup Z = 7,66 mm (.300") #4-40 with pushfit, only OL4				Shell Plating Modification Code blank = Yellow chromate over zinc A197 = Pure Tin over Nickel (socket side only) RoHS K87 = Pure Tin over Nickel (pin shell with grounding dimples) RoHS				
Layout (Total number of contacts + number of size 8 cavities) Shell Size E: 2W2, 2WK2, 5W1 Shell Size A: 3W3, 3WK3, 7W2, 11W1 Shell Size B: 5W5, 9W4, 13W3, 17W2, 21W1 Shell Size C: 8W8, 13W6, 17W5, 21WA4, 25W3, 27W2 Shell Size D: 24W7, 36W4, 43W2, 47W1 W = Empty size 8 cavities C = 75 Ohm Coax installed (straight or 90°) X = 50 Ohm Coax installed (straight or 90°) H = High power installed (straight) P = High power installed (Euro, 90° only) V = High voltage installed (available in straight PC only) G = Guide pin or guide socket installed R = Mini High Power 90° installed				Contact Plating Modification Code blank = performance class 3 (50 mating cycles) A191 = performance class 2 (200 mating cycles) A190 = performance class 1 (500 mating cycles)				
Contact Gender P = Pin /Male (plug) S = Socket /Female (receptacle)				Contact Tail Modifier blank = Solder cup (size 8 contacts not loaded on these versions) OL2 = Not standard, please call factory OL3 = Solder pin /pc tail, straight 1A0N = Without mouting bracket, hole dia. 3,05 mm 1A5N = Plastic bracket with bushing dia. 3,05 mm 1A6N = Plastic bracket with #4-40 threaded post 1A7N = Metal bracket and #4-40 captive nut 1A8N = Metal bracket with #4-40 threaded post 1A9N = Metal bracket and M3 captive nut 1ADN = Plastic bracket with grounding bracket and bushing dia. 3,05 mm 1AFN = Metal bracket with bushing dia. 3,05 mm 1AGN = Plastic bracket with grounding bracket and M3 threaded post 1AHN = Metal bracket with M3 threaded post 1AJN = Plastic bracket with grounding bracket and #4-40 threaded post 1APN = Plastic bracket with M3 threaded post – Not available, please use 1AHN instead 1ATN = Plastic bracket and M3 captive nut – Not available, please use 1A9N instead 1AUN = Plastic bracket and #4-40 captive nut 1AVN = Plastic bracket with grounding bracket and captive M3 nut – Not available, please use 1A9N instead 1AWN = Plastic bracket with grounding bracket and captive #4-40 nut – Not available, please use 1A7N instead 1AEN = 90° low profile metal bracket with M3 captive nut 1AAN = Low profile metal bracket and #4-40 captive nut – Not available, please use 1A7N instead 1ABN = Low profile metal bracket and M3 threaded post – Not available, please use 1AHN instead 1ACN = Low profile metal bracket and #4-40 threaded post – Not available, please use 1A8N instead 1ALN = Low profile metal bracket and bushing dia. 3,05 mm – Not available, please use 1AFN instead				
Code only applicable for Pressfit High Power size 8 contact P00 = Pressfit High power PCB dia 2,9 mm P01 = Pressfit High power PCB dia 3,1 mm P02 = Pressfit High power PCB dia 3,5 mm								



Connect with your ITT Cannon
representative today or visit us at
www.ittcannon.com

Connect with the experts.

From rocket launchers and satellite systems, to ruggedized military transports and aerospace applications, we connect the world's most important information with the people who need it.



ENGINEERED FOR LIFE

cannon

CHINA—Shenzhen City
+86.755.2726.7888

GERMANY—Weinstadt
+49.7151.699.0

INDIA—Bangalore
+91 22 67843000

JAPAN—Kanagawa
+81.462.57.2010

SINGAPORE
+65 66974205

USA—Irvine, CA
+1.800.854.3028

FRANCE
+33.1.60.04.93.93

HONG KONG
+852.2732.2720

ITALY—Linate
+39.02938721

MEXICO—Nogales
+52.631.311005

UK—Basingstoke
+44.1256.347400