

C 091 A

Female cable connector,
screw locking,
straight



Cable diameter 4-6 mm



Cable diameter 6-8 mm



Cable diameter 4-6 mm



Cable diameter 4-6 mm

Description	Drawing	No. of cont.	Part Number solder termination		Part Number Crimp termination ¹⁾
			Contact plating silver	Contact plating gold ²⁾	
Female cable connector, for cable diameter 4-6 mm, termination: solder or crimp, contact plating: silver or gold.		2	T 3201 001	T 3201 018	—
		3 ³⁾	T 3261 001	T 3261 018	T 3261 551
		4 ³⁾	T 3301 001	T 3301 018	T 3301 551
		5	T 3361 001	T 3361 018	T 3361 551
		5 S ³⁾	T 3361 010	T 3357 018 ⁴⁾	T 3357 551
		6 ³⁾	T 3401 001	T 3401 018	T 3401 551
		7	T 3476 001	T 3476 018	T 3476 551
		7 ³⁾	T 3485 001	T 3485 018	T 3485 551
		8 ³⁾	T 3505 001	T 3505 018	T 3505 551
		12	T 3636 001	T 3636 000	—
		14	T 3651 001	T 3651 000	—
		2	T 3201 002	T 3201 028	—
		3 ³⁾	T 3261 002	T 3261 028	T 3261 552 ⁴⁾
		4 ³⁾	T 3301 002	T 3301 028	T 3301 552 ⁴⁾
Female cable connector, for cable diameter 6-8 mm, termination: solder or crimp, with clamping ring, contact plating: silver or gold.		5	T 3361 002	T 3361 028	T 3361 552
		5 S ³⁾	T 3361 020	T 3357 028 ⁴⁾	T 3357 552 ⁴⁾
		6 ³⁾	T 3401 002	T 3401 028	T 3401 552 ⁴⁾
		7	T 3476 002	T 3476 028	T 3476 552
		7 ³⁾	T 3485 002	T 3485 028	T 3485 552 ⁴⁾
		8 ³⁾	T 3505 002	T 3505 028	T 3505 552
		12	—	T 3636 002	—
		14	—	T 3651 002	—
		2	—	—	—
		3 ³⁾	T 3261 004	T 3261 048	T 3261 554 ⁴⁾
		4 ³⁾	T 3301 004	T 3301 048	T 3301 554
		5	T 3361 004	T 3361 048 ⁴⁾	T 3361 554 ⁴⁾
		5 S ³⁾	T 3357 004	T 3357 048 ⁴⁾	T 3357 554
		6 ³⁾	T 3401 004	T 3401 048	T 3401 554 ⁴⁾
		7	T 3476 004	T 3476 048	T 3476 554 ⁴⁾
Female cable connector, for cable diameter 4-6 mm, termination: solder or crimp, contact plating: silver or gold.		7 ³⁾	T 3485 004	T 3485 048	T 3485 554 ⁴⁾
		8 ³⁾	T 3505 004	T 3505 048	T 3505 554
		12	—	T 3636 004	—
		14	—	T 3651 004	—
		2	T 3201 013	—	—
		3 ³⁾	T 3261 013	—	—
		4 ³⁾	T 3301 013	—	—
		5	T 3361 013	—	—
		5 S ³⁾	T 3361 130	—	—
		6 ³⁾	T 3401 013	—	—
		7	T 3476 013	T 3476 038	—
		7 ³⁾	T 3485 013	—	—
		8 ³⁾	T 3505 013	—	—
		12	—	—	—
		14	—	—	—
Female cable connector, for cable diameter 4-6 mm, solder termination, plastic coated coupling ring, contact plating: silver.		2	T 3201 013	—	—
		3 ³⁾	T 3261 013	—	—
		4 ³⁾	T 3301 013	—	—
		5	T 3361 013	—	—
		5 S ³⁾	T 3361 130	—	—
		6 ³⁾	T 3401 013	—	—
		7	T 3476 013	T 3476 038	—
		7 ³⁾	T 3485 013	—	—
		8 ³⁾	T 3505 013	—	—
		12	—	—	—
		14	—	—	—

¹⁾ Please order crimp contacts separately, see page 43

²⁾ See remark page 6

³⁾ Contact order for DIN EN 60 130-9

⁴⁾ Available upon request.