



Freier Steckverbinder, gerade, Endgehäuse mit Klemme und Tülle.  
 Free connector, straight type, backshell with cable and bushing.  
 Mobile droite, raccord avec brides et manchon.

Beispiel / Example / Exemple  
 - VG95234D-18-1SN  
 - GCB3106E-18-1SNB  
 - GCA3106E-18-1SNB

| Gehäusegröße /<br>Shell size /<br>Taille de boîtier | d <sub>1</sub><br>max. | d <sub>2</sub> <sup>(2)</sup><br>max. | l <sub>1</sub><br>max. | l <sub>2</sub><br>max. | l <sub>3</sub><br>max. | Masse /<br>Mass<br>g max. <sup>(1)</sup> |
|---|------------------------|---------------------------------------|------------------------|------------------------|------------------------|--|
| 10SL  | 22,8                   | 6,5                                   | 115                    | 58                     | 22,7                   | 30                                       |
| 14S   | 29,2                   | 9,0                                   | 115                    | 60                     | 27,5                   | 44                                       |
| 16S   | 32,0                   | 11,0                                  | 115                    | 60                     | 30,0                   | 54                                       |
| 16  | 32,0                   | 11,0                                  | 120                    | 70                     | 30,0                   | 62                                       |
| 18  | 36,5                   | 14,2                                  | 120                    | 75                     | 33,0                   | 70                                       |
| 20  | 39,9                   | 15,8                                  | 120                    | 75                     | 37,5                   | 85                                       |
| 22  | 43,1                   | 15,8                                  | 120                    | 75                     | 37,5                   | 92                                       |
| 24  | 46,6                   | 21,4                                  | 120                    | 90                     | 43,3                   | 127                                      |
| 28  | 53,4                   | 21,4                                  | 120                    | 90                     | 48,0                   | 154                                      |
| 32  | 60,1                   | 26,7                                  | 120                    | 90                     | 55,0                   | 199                                      |
| 36  | 66,3                   | 31,7                                  | 130                    | 100                    | 58,0                   | 260                                      |

<sup>(1)</sup> Masse ohne Kontakteinsätze / Mass without contact inserts / Masse sans inserts

<sup>(2)</sup> Für max. zulässigen Kabeldurchmesser / For max. admissible cable diameter / Pour diamètre de câble maxi admissible