

# PART NUMBERING

## CONNECTORS

SERIES	GENDER	WIRING PROTOCOL	SHELL STYLE	FINISH	SHELL SIZE	NO. OF CONTACTS
WM	X	XXX-	XX	RX	X	X
WM	M - Male (Sprung contact)  F - Female (Fixed PCB)	000 - Solder 001 - IDC with 28 awg USB 002 - IDC with 26 awg USB	00 - Wall mount 01 - Supplied without mounting feature 02 - Box-mount PCB 04 - MOLLE loop mount 06 - Free connector 07 - Jam-nut mount PCB	RZ - Black RW - Olive-drab RD - Sand	2	7

Please note that equipment mount styles 02, 07 are in development and the designs are still being finalised. This catalogue will be updated to provide dimensional and performance details once the design work is completed.

## ACCESSORIES

### PROTECTIVE CAPS

SERIES	GENDER	STYLE	FINISH	SHELL SIZE	ATTACHMENT	EYELET
WM	X	-PC	-RX	-X	-X	-X
WM	F - Cap for male M - Cap for female	PC	RZ - Black RW - Olive-drab RD - Sand	2	0 - None supplied 1 - Terylene cord 2 - Wire rope	0 - None supplied 1 - Small 2 - Large 3 - Crimp ferrule

### STOWAGE RECEPTACLES

SERIES	GENDER	STYLE	FINISH	SHELL SIZE
WM	X	-SRX	-RX	-X
WM	F - Stowage for male M - Stowage for female	SR0 - Wall Mount SR4 - MOLLE	RZ - Black RW - Olive-drab RD - Sand	2